



ADPRO's latest generation of video transmission products are the benchmark for live transmission of outstanding quality video and audio. Developed to satisfy the most demanding requirements, ADPRO FastVu encompasses years of technological leadership of the video transmission market for security and surveillance applications.

ADPRO FastVu utilises LAN/WAN network systems or data links to protect and monitor your sites, 24 hours a day, anywhere in the world.

Three models are available. Choose from a 20 channel rackmount Transceiver or 10 channel Transmitter only models in wall or rackmount cases.

All models have integrated high-speed pre-alarm capture, multiple levels of video resolution, superb quality bi-directional audio, high speed PTZ camera control and ADPRO AMK-300 external keyboard/joystick, making ADPRO FastVu the product of choice.

ADPRO[®] FastVu

Video Transmission System

Features:

- Live video over digital networks.
- RJ45 connection to Ethernet and V.24 interface to 230 kbps with secure poll and comms link fallback options.
- User selectable image transmission rate provides efficient throttle control of overall network bandwidth.
- Exceptional colour or monochrome picture quality with full colour range and 256 grey levels. PAL selectable.
- Simultaneous multiple pre and post alarm image capture and management.
- On board storage of six post-alarm sequences (three images each) and 180 pre-alarm images.
- High quality audio transmission with automatic gain control and echo cancellation.
- On-screen setup in English, French, Italian, German, Spanish, Portuguese, simplified Chinese and Korean.
- Operates with ADPRO Video Central for sophisticated PC based central control and management.
- Direct microphone input and loudspeaker output.
- A wide range of PTZ protocols support a variety of camera stations with variable speed joystick control.
- Option to support Down-the-Coax telemetry.
- 20 (or 10) video and alarm inputs with remote arming /isolation, entry/ exit paths and delays.
- Auto sequencing and multi screen display.
- Option to support alarm input tamper detection.

ADPRO® FastVu Video Transmission System

Outstanding Picture Quality

Using state of the art digital video compression techniques, ADPRO FastVu provides rapid initial image transmission and the fastest updates of all activity. Outstanding picture quality is maintained regardless of the link speed.

Comprehensive Remote Control

Industry standard serial interfaces allow easy integration with a wide variety of telemetry, matrix switcher, access control and image storage systems.

No Alarms Missed

Automatic transmission and storage of high quality snapshot image sequences from six concurrent alarm events eliminates the threat of decoy alarms.

Rapid and accurate assessment of site activity is provided by simultaneous display of high quality stored alarm and live images in a split screen format.

For complete analysis, the pre-alarm feature can be set to capture video images from any or all channels.

High Quality Audio

Integrated listening ability assists in the alarm verification process, while transmission of the operator's voice to the site provides instant intruder control. ADPRO FastVu uses sophisticated audio compression techniques to ensure that high quality, bi-directional audio uses the minimum possible bandwidth of the communications channel.

Specifications

Video Inputs

20 BNC video channel inputs (model 2020). 10 BNC video channel inputs (models 2010 and 3010). 1V p/p video input, 75-ohm or high impedance (switchable). Colour or monochrome selection, automatic or manual gain control per channel.

Video Outputs

1x BNC into a 75-ohm Output connection.
1x S-VIDEO (model 2020 only).

Alarm Inputs

20 external alarm inputs (10 on model 2010 and 3010) that trigger an alarm and store images from the corresponding video channel. Programmable for contact opening or closure.
Optional End of Line sensing with a VM25 I/O Expander unit.

Control Outputs

Transmitter: 3 x open drain control outputs. Option of 10 with VM25 I/O Expander. 1 x general alarm relay with contacts (N/O, N/C).

Pre-Alarm Video Capture

Up to 180 high quality pre-alarm images are captured. Time interval between images on the channel selectable from 0.5-9.0 seconds.

Post Alarm Video Capture

3 high quality images are captured for each of up to 6 concurrent alarms. Time interval between images are selectable from 0.5 to 9 seconds.

Image Transmission Rate

The first image transmission time and subsequent update rate is a function of the selected picture quality, scene complexity and communication interfaces. User selectable maximum transmission rate for efficient throttle control of network bandwidth. Typical update rates with 10% scene changes.

Ethernet: = 25 images/second

ISDN: 128k = 25 images/second

PSTN: 33k6 = 12.5 images/second

Image Resolution

Colour or black and white.

Intensity - 256 grey levels; Maximum image resolution over 400 horizontal TV lines.

Resolutions available (PAL):

4 CIF PAL: 704 x 576 pixels

2 CIF PAL: 704 x 288 pixels

CIF PAL: 352 x 288 pixels

QCIF PAL: 176 x 144 pixels

Audio Input/Output

Bi-directional audio communication between Transmitter and Receiver on links greater than 14.4 kbps, 300 Hz to 3.3 kHz bandwidth, 1 V p/p (typ), 1.5 V p/p (max). Separate inputs for microphone and line plus output for external speaker.

Connector for VM22A Multiple Audio Switcher.

ADPRO® FastVu Video Transmission System

Serial Data Port

External bi-directional RS232 data link. Programmable baud rate, data bits, stop bits, flow control, 57.6 kbps (max.).

PTZ Telemetry Port

Differential balanced input/output RS485 serial port. (Used for control of PTZ telemetry stations). 'Down-the-Coax' telemetry supported via optional hardware module.

Communication Links

Network

10BaseT Ethernet port supporting TCP/IP.

Serial

V.24 interface (8 data bits, no parity, max baud rate = 230 kbps) via a 9 pin D connector. Supports Hayes AT compatible PSTN or ISDN modems in a dial up or leased line configuration. Support for Multilink PPP or V.120 data protocol over ISDN.

Keyboard Port

Keyboard or Computer port for computer control via IEC Protocol support.

System Control & Setup

Operator control via ADPRO AMK-300 External Keyboard or Video Central Software.

Software Upgrades

New software upgrades are loaded via a PC.

Power Requirements

11 - 18 VDC, 15 Watts (max) at 12 VDC supplied via an external plugpack.

Construction and Dimensions (model 2020 and 2010)

Standard 19" rackmount, 2U high subrack to DIN4194.
482 mm W x 44.4 mm H x 210 mm L.

Construction and Dimensions (model 3010)

Unsealed, wall mounted metal cabinet 380 mm H x 370 mm W x 130 mm D.

Weight

Rackmount - 3 kilograms

Wallmount - 4.5 kilograms

Operating Conditions

Operating temperature range 0° C - 50° C

Humidity less than 90% non-condensing.

EMC Compliance

Emissions: Class A compliance to EN55022, CISPR 22, AS3548, FCC Part 15.

Mains Harmonic Emissions to EN61000-3-2.

Voltage Fluctuations & Flicker to EN61000-3-3.

Immunity: EN50130-4 (Alarm Systems Product Family Immunity Standard).

Immunity to Digital Radio Telephones to

ENV 50141.

Safety Compliance

IEC 60950 : 1991 +A1, A2, A3 & A4 when used with the supplied AC Power Adaptor.

Warranty

Twenty Four (24) months.

Accessories

- ADPRO AMK-300 Keyboard
- ADPRO VM87 Handheld Programmer
- ADPRO VM22A Audio Switcher
- ADPRO VM23 Intercom Handset
- ADPRO VM25 I/O Expander

Ordering Information

AFV-2020-TCVR 20 Channel Transceiver - rackmount.

AFV-2010-TX 10 Channel Transmitter - rackmount.

AFV-3010-TX 10 Channel Transmitter - wallmount.

AM-DTCT-2 'Down-the-Coax' telemetry module option.

Tyco Safety Products Part Number

AMK 300	604.001.138
VM87	604.001.144
VM22A	604.001.143
VM23	604.0012.148
VM25	604.001.145
604.001.140	Fast Vu 2020 20 Channel Rack Mount Transceiver
	200710 AFV-2020-TCVR
604.001.141	Fast Vu 2010 10 Channel Rack Mount Transceiver
	200827 AFV-2010-TCVR
604.001.142	Fast Vu 3010 10 Channel Wall Mount Transceiver
	200907 AFV-3010-TX

SPECIFICATIONS

For further information on how we can help you please visit our website at www.tycofis.com or e-mail us on tycofis@tycoint.com. The right is reserved to modify or withdraw any product or service without notice. PSS144TFIS Issue 2 June 2006 © 2006

a vital part of your world

tyco

*Fire & Integrated
Solutions*